


TS-1GP4G-2POT+RF



GPON ONU with LAN **4x100Mbps RJ45, 2xpots RJ11, 1xRF CATV**

PRODUCT OVERVIEW :

TELESYSTEM TS-1GP4G-2POT+RF is a new generation smart ONU with 4x100M ports for integrated multi-service networks. It is complied with the international standard ITU-T G.9844/988 and PRC Communication Industry Standard GPON ONU in Access Technology Requirements.

PRODUCT CHARACTERISTICS :

- Excellent Access Capacity:** It supports the PON transmission rate of downlink 2.5Gbps/ uplink 1.25Gbps. Connected with TELESYSTEM OLTs, it can realize 1:128 splitting ratio. The covering radius of the network can reach to 20km.
- Secure Service Carrying Ability:** For ensuring the secure service carrying ability of ONU, TELESYSTEM has developed techniques including VLAN, STP, port isolation, ACL, QoS and Broadcast Storm Control.
- High Service Control Capability:** It supports DBA and Rate-Limit. It supports advanced dynamic bandwidth distribution and accurate bandwidth limit, which enables users to share 2.5Gbps bandwidth resource appropriately. It also supports QOS function, which guarantees a reliable service quality and service priority.
- Rich OMCI Functions:** It supports the standard OMCI defined by ITU-T, including configuration, alarm, performance monitoring, fault isolation and security management, and it also supports private OMIC defined by TELESYSTEM.
- Complete Interaction Capacity:** It is complied with ITU-T G.984/988 and relevant requirements for PRC Community Industry Standard GEPON ONU in Access Technology Requirements and China Telecom EPON Technical Requirement CTC2.0.
- Advanced Energy-saving Technique:** It supports the “GreenTouch” architecture and “Smart@CHIP”.

TECHNICAL PARAMETERS :

Attributes	TS-1GP4G-2POT+RF
User trial interface	4x 10/100 Mbps auto adaptive Ethernet interfaces. 10/100M Full/Half, RJ45 connector
PON interface	downlink 2.5Gbps / uplink 1.25Gbps The network covering radius: 20km Type of the optical interface: SC/UPC Hi-sensible optical receiver: -27dBm Radiation power: 0.5 ~5dBm Security: ONU authentication mechanism

Standards	<p>ITU-T G.984/G.988</p> <p>PRC Community Industry Standard GEAPON ONU in Access Technology Requirements</p> <p>IEEE 802.1D, Spanning Tree</p> <p>IEEE 802.1Q, VLAN</p> <p>IEEE 802.1w, RSTP</p> <p>ITU-T Y.1291</p>
CATV Interface	1 RF output Female F-Type Connector
POT interface	2*RJ11
VLAN	<p>Supports 64 VLANs (1~4094)</p> <p>Port based VLAN</p> <p>IEEE 802.1Q VLAN</p> <p>CTC2.0 defined VLAN</p>
Multicast	<p>IGMP-Snooping</p> <p>CTC defined dynamic multicast</p> <p>MLD-Snooping</p>
QoS	<p>Backpressure flow control (half duplex)</p> <p>IEEE 802.3x flow control (full duplex)</p> <p>Head Of Line (HOL) mechanism</p> <p>IEEE 802.1p, CoS</p> <p>four priority queues on each port</p> <p>WR, SP and FIFO</p> <p>Rate limit</p>
Reliability	<p>Loop detect</p> <p>Dying-Gasp</p>

Security	Limitation to the number of MAC addresses on the port Port protection Port storm control
Management	CLI, Web, SNMP and TELNET Software upgrade through TFTP and WEB Local syslog or server syslog
Dimensions mm (W×D×H)	130 x 100 x 28 Installation: plug and play
Heat dissipation	Supports long-time use (For instance, 24 hours); The device running hot will not affect its performance or cause it break down.
Environment requirements	Operating environment: 0°C~45°C; 10%~85% non-condensation Storage environment: -40°C~80°C; 5%~95% non-condensation
Power supply	DC12V/0.5A (external adaptor power supply)
Power consumption	<6W