

TS-SF1005 : 5Port10/100Mbps Fast Ethernet Switch
Model No : TS-SF1005

Packing details

Product Size: 113x85x29MM
 Product Weight:0.25KG
 1pcs per box
 Box Size: 185x143x62mm BoxWeight:0.45KG
 Carton Size:475x390x300MM
 24pcs per Carton
 Net Weight :13.2KG ;Gross Weight:13.9KG



Product Description :

TS-SF1005, 10Base-T/100Base-TX switch is a high performance Fast Ethernet switch and designed for the network core. provides 5 10/100Mbps ports that can significantly improve the performance of your network’s backbone, and deliver the throughput needed to support a broad range of advanced network applications. With high performance bandwidth, it provides the quickest solution to meeting the growing demands.

Product Features :

- Conforms to IEEE802.3,IEEE802.3u and 802.3ab standard
- Supports IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode
- Provides 5 10/100Mbps auto-negotiation RJ45 port
- Auto-MDI/MDIX eliminates the need for crossover cables
- Supports MAC address auto-learning and auto-aging
- Supports Auto-negotiation ports provide smart integration between 10Mbps and 100Mbps
- Desktop or wall-mounting design
- Plug and Play design simplifies installation

Specification :

Standards and Protocols	IEEE802.3, 802.3u, 802.3ab, 802.3x CSMA/CD, TCP/IP
Basic Function	Wire-speed Performance
	MAC Address Auto-Learning and Auto-aging
	IEEE802.3x flow control for Full-Duplex Mode and backpressure for Half-Duplex Mode
Backbound Bandwidth	10Gbps
MAC Address Table	1k
Transmission Method	Store-and-Forward
Ports	5 10/100Mbps Auto-Negotiation RJ45 ports (Auto

	MDI/MDIX)
Network Media	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Û STP (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Û STP (maximum 100m)
LED Indicators	Power, Link/Act
Certification	CE
RoHS	RoHS compliance
Dimension (L*W*H)	113x85x29mm
Environment	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Power	External Power Adapter (12V/0.6A)
Warranty	1 Year Limited