

DOM Fiber Optic Splice Closure 72 cores (can be used for 96)



Type: MANCH.FO.72 DOM

Provides with 4 fiber cables in-out round ports, available for aerial and underground application. This product is made of high quality engineering plastic. The cover and the base are filled with silicon rubber and sealed with hoop. The entry ports are sealed with thread parts. It can be reopened repeatedly after being sealed.

Item	ANCH.FO.72 DOM
Dimension(mm)	Φ190X410
Weight(kg)	2.34
Cable diameter(mm)	Φ7-Φ22mm
Cable entry ports	2 cable entry ports on each end
Max capacity of fiber splice	24 single
Max capacity of splice trays	Equipped with 3pcs, Max 4 pcs
Max capacity	96 single
Structure of cable entry port	Thread mechanical sealing
Sealing structure	Silicon gum material

Kit contents:

Description	Quantity
Splice Protector Tube	According to fiber cores
Marking Note	1 pc
Abrasive Cloth	1 pc
Special wrench	1 pc
Sticky Cincture	1 coil
Sticky Cincture	1 coil
Earthing Wire	1 stick
Fiber Buffer Tube	According to request
Metal Hoop	1 set
Plastic Hoop	1 set
O Sealing Ring	1 big, 1 small
Fiber Protector Tube	According to splice tray
Cables Ties	4xsplice tray