

## TS-FBSM2K- FC : BOBINES D'AMORCE FC-FC SM, 2 Km

### Description:

Designed to aid in the testing of fiber optic cable when using an OTDR. The OTDR Launch Fiber box is used with Optical Time Domain Reflectometers (OTDRs) to help minimize the effects of the OTDRs launch pulse on measurement uncertainty. Available in many different configurations and fiber lengths.

### Features:

1. Pulse Suppressor, Launch Box, Delay Line,

Installation/Testing, Training, Calibration

2. Compound Latch for positive seal and easy opening with locking feature

3. Non metal construction will not dent, corrode, or conduct electricity

4. Water and dust prove allowing the unit to be taken into almost any environment

5. Case can house up to 2,000 meters of fiber

6. Auto Purge Valve for changes in altitude and temperature



### Specifications:

Length x Width x Height	9.37" x 5.56" x 2.62"
Material	SR Polypropylene
Weight	0.75 kg (without fiber)
Operating temperature	-40° to +55°C
Typical Loss	< 0.5dB @ 1310nm for 2000 meters

### Models & Références :

TS-FBSM1K	BOBINES D'AMORCE FC/FC SM, 1 Km
TS-FBSM1K- SC	BOBINES D'AMORCE SC-SC SM, 1 Km
TS-FBSM2K- FC	BOBINES D'AMORCE FC-FC SM, 2 Km