

TS-MCoax16:

16 Channels Forward HD TVI/CVI/AHD/CVBS Video to Fiber Converter



Introduction

HD TVI/CVI/AHD/CVBS 16 in 1 Video to Fiber Converter can simultaneously transmit 16 channels HD TVI/CVI/AHD/CVBS video over one single-mode optical fiber. Electronic and optical adjustments are never required. LED indicators are provided for instantly monitoring system status. Devices are available for either standalone or rack-mount installation, which is suitable for different working environment. HD TVI/CVI/AHD/CVBS Video to fiber converters adopt the advanced uncompressed HD composite video and high velocity digital optical transmission technologies which convert the composite signals to optical signals to achieve long distance for the HD CCTV installation.

Features

- Non-compression coding technology
- Automatically identify formats of input videos
- Support transmission of HD TVI/CVI/AHD/CVBS signal and controlling data simultaneously through fiber optic cable
- DC 5V power supply
- Support 720p/25、720p/30、720p/50、720p/60、1080p/25、1080p/30 videos etc
- Through LED indicators to inform its functional mode
- Industrial wide range of operational temperature
- Plug and play, simple installation


Application

- ✧ City traffic monitoring system
- ✧ Public security, safe city monitoring system
- ✧ Highway security protection, charging system
- ✧ Building, campus monitoring net
- ✧ Industrial monitoring (airport, chemical industrial, steel, oil, railway, water conservancy, mine, etc)
- ✧ Military monitoring (storehouse, frontier defense, guard, nation defense, etc)
- ✧ electric power, oilfield, television program transmission system
- ✧ Gymnasium (live video, audio transmission)

Distributeur: SARL ALIEF Address: lot n°: 1, Gpe 13, Hamiz, Dar El Beida, Alger, ALGERIE

Standard : 0560 271 399 , 0560 261 451 mobilis : 0661 528 551 Tel fix : +213 (0) 23 858 510 , (0)23 858 511 , (0)23 865 001
 Fax : +213 (0) 23 858 514 web: www.alief.dz emails: com@alief.dz, com@alief-dz.com

HD TVI/CVI/AHD/CVBS 720P/960P/1080P Series Connection Diagram



Technical Specification

Feature		Description
Optical	Fiber Type	Single-mode fiber (9/125um)
	Fiber Connector	FC
	Distance	20KM (Single-mode fiber)
	Wavelength	Transmitter:T1310nm, R1550nm.
		Receiver:T1550nm,R1310nm.
Fiber Power	-9~ -5dBm	

	Rx Sensitivity	-24dBm
Video	Video Interface Number	16 channels
	Physical Interface	BNC
	Tx Input level	>500mVp-p
	Rx Output level	1-1.2Vp-p
	Bandwidth of Video	50M(720P) 100M(1080P)
	Differential Phase	≤ 2
	Differential Gain	≤ 2%
	Input/Output Impedance	75 Ω
	Surge Protection	10/700us:(1-1.5kv)
	Sampling Digit	10 Bit
	Sampling Frequency	60Mhz
Data	Physical Interface	The industry standard connecting terminal
	Interface Signal	RS485/RS422/RS232/Manchester
	Baud Rate	0-400Kbps
	BER	< 10 ⁻⁹
	Operation Mode	Full duplex / half duplex
Environmental Demand	Environmental Temperature	-30°C~+75°C
	Storage Environment	-40°C~+85°C
	Relative Humidity	0-95% (no condensation)
	Mean Time Between Failures(MTBF)	≥100 000 hours
	EPS	DC5V

Order Information

Model No.	Description
TS-MCoax16	16 x TVI/CVI/AHD/CVBS forward video + 1 x return RS485 data, SM FC
Note: 1. Power supply provided by user or ordered additionally 2. FC connector as default, SC/ST/LC as request	

Remark: To meet the needs of our customers and help them to realize their projects, we also can manufacture the products according to customers requirements.