

TS-KJFTP6A-SW : Cat6A STP RJ45 180 degree Tool Free Keystone Jack With Dust Shutter.



Description du product

RJ45 Cat.6A Modular Keystone Jack Shielded Tool-free Connection Design. 50u" gold-plated RJ45 Jack and suitable for 23-26AWG stranded and solid wire. Meeting the international standard ISO/IEC 60603-7-51 and the ANSI/TIA-568-C.2 requirements.

Features:

1. Full shielded with a rugged cast-encased rear, utilizing an innovative tool free termination.
2. Easy reliable and stable quality by insert-molding and press-fit assembly process.
3. Fits for 1U 24 port and 1U 48 port keystone panel.
4. Suitable for cabling from the smallest home networks to very large data centers.
5. Cable entrance diameter range: 5.5mm-9.0mm.
6. Insulation diameter range: 0.95mm-1.62mm.
7. Solid and Stranded conductor: 23-26AWG.

Material:

Jacking Housing: Zinc die-casting with Nickel plated
 Spring Pin: Phosphor Bronze, Nickel undercoat, Gold plating 50u"
 Pin Holder: PBT
 PCB: FR-4

Description	Parameter
Contact resistance(max)	100m ohm
Insulation resistance(min)	500Mohm
Return loss(dB)	5.8dB
Next(dB)	4.7dB
Ps next(dB)	5.5dB