

PAN24UTP5E & PAN24FTP6**Models:**

PAN24UTP5E	Panneau de brassage, 24 port UTP, Cat 5e, 19" rack mountable.
PAN24FTP6	Panneau de brassage, 24 port FTP, Cat 6, 19" rack mountable

Description :

- Using the standard of 110 wire tools.
- Cable or fiber optic cable termination and connection devices.
- On the patch panel for interconnection or transfer operation.
- Patch panel as the core product of cabling system, the flexible transfer plays a transmission signal, flexibility in the allocation, clear structure.
- Adapt to different needs, voice / data points exchange, to adapt to the different LAN topologies electrical according to UL 1863
- Current rating : 1.5 Amp Max.
- Voltage rating : 150 Volts
- Contact resistance : 20 m-ohm
- Insulation Resistance: 500M-ohm
- Dielectric Withstand Voltage: 1000 V AC RMS, 60Hz 1min
- Ethernet applications>1000mbps,10/100mbps
- Application: ATM or Ethernet 2.4G network
- Durability : 250 mating

Specifications :

- Meet TIA/EIA-568-A and TIA/EIA-568-B Category 5E cat6 requirements.
- Meet TIA/EIA TSB-40
- Meet ISO/IEC Generic Cabling Standard 11801
- Meet CENELEC Generic Cabling Standard EN50173
- Termination: 110 Type & Krone type

Advantage :

- Reduce installation and operating costs
- Large space for the positive identification
- The port is easy to identify
- Consistent with the standard 19-inch rack mount.

